

6-40GHz 八路功分器 8-Way Power Divider

频率范围 Frequency Range	6~40 GHz
插入损耗 Insertion Loss	≤3.2 dB（不含 9dB 理论损耗）
输入驻波 Input VSWR	≤2.20
输出驻波 Output VSWR	≤1.60
隔离度 Isolation	≥15dB Typ.22dB
幅度平衡 Amplitude Balance	±0.7 dB
相位平衡 Phase Balance	±7°
功率容量 Power Handling	功分用时 20W，合路用时 1W
接口形式 Connectors	2.92mm-Female
表面处理 Surface Finish	本色导电氧化

Technical drawing of a rectangular plate with dimensions in inches and millimeters. The drawing includes a top view and a side view.

Top View Dimensions:

- Overall width: 104 [4.094]
- Overall height: 40 [1.575]
- Distance from top edge to center hole: 3 [0.118]
- Distance from center hole to bottom edge: 31 [1.220]
- Distance from left edge to center hole: 99 [3.898]
- Distance from right edge to center hole: 99 [3.898]
- Distance from left edge to mounting holes: 6 [.236]
- Distance between mounting holes: 13 [.512]
- Distance from center hole to mounting holes: 104 [4.094]
- Distance from center hole to corner holes: 4-Ø2.3 [0.09] THRU

Side View Dimensions:

- Overall thickness: 10 [.394]
- Height of mounting holes: 5 [.197]