

► ZJA系列互联柔性线缆组件



产品规格书																							
技术指标																							
特性阻抗	50Ω																						
频率范围	DC~26.5GHz																						
电压驻波比	≤1.25																						
插入损耗	$\sqrt{\text{GHz}} \times 0.08 + L \times \text{dB/M}$																						
外形尺寸图																							
<p>★ 注： L:组件长度; 2:热缩套管; 3:标签 LOGO; 4:线缆;</p>																							
组件选型																							
<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">线缆型号</div>	<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">接头1/接头2</div>	<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">长度</div>	<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;">频率</div>																				
<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">ZJA047</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">ZJA086</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">ZJA141</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">ZJA250</div>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">S: SMA</td> <td style="width: 50%;">M: 公头</td> </tr> <tr> <td>N: N</td> <td>F: 母头</td> </tr> <tr> <td>T: TNC</td> <td>WM: 弯公头</td> </tr> <tr> <td>35: 3.5mm</td> <td>WF: 弯母头</td> </tr> <tr> <td>K: 2.92mm</td> <td></td> </tr> <tr> <td>24: 2.4mm</td> <td></td> </tr> <tr> <td>SP: SMP</td> <td></td> </tr> <tr> <td>2SP: SSMP</td> <td></td> </tr> <tr> <td>185: 1.85mm</td> <td></td> </tr> <tr> <td>1: 1.0mm</td> <td></td> </tr> </table>	S: SMA	M: 公头	N: N	F: 母头	T: TNC	WM: 弯公头	35: 3.5mm	WF: 弯母头	K: 2.92mm		24: 2.4mm		SP: SMP		2SP: SSMP		185: 1.85mm		1: 1.0mm		<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">例:</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">2m:2m</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">20mm:20mm</div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">例:</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">0/0.6: DC~600MHz</div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">0/6: DC~6GHz</div>
S: SMA	M: 公头																						
N: N	F: 母头																						
T: TNC	WM: 弯公头																						
35: 3.5mm	WF: 弯母头																						
K: 2.92mm																							
24: 2.4mm																							
SP: SMP																							
2SP: SSMP																							
185: 1.85mm																							
1: 1.0mm																							